

DAILY



Daily LINE – Diesel Euro VI/C

3520L	4100	4100L
 16+1	 19+1	 22+1
	 19/16+1 1.2 m³ luggage	 22/19+1 1.2 m³ luggage
 16/9+1w+1	 19/14+1w+1	 22/17+1w+1
	 19/12+2w+1	 22/15+2w+1

WHEELBASE (mm)	3520L	4100	4100L
LENGTH (mm)	5950	7120	7515
WIDTH (mm)	2052	2052	2174
OVERALL HEIGHT (mm)	2784	2784	2905
INTERNAL HEIGHT (mm)	1820		
FRONT OVERHANG (mm)	1008		
REAR OVERHANG (mm)	1422	2012	2407
FRONT TRACK (mm)	1724	1724	1725
REAR TRACK (mm)	1540	1540	1661
TURNING DIAMETER WALL TO WALL (mm)	12744	15190	14758
TURNING DIAMETER KERB TO KERB (mm)	12084	14564	14108
WEIGHTS			
MODEL	40C	50C	60C
GROSS VEHICLE MASS (kg)	4500	5600	6100
FRONT AXLE PLATED MASS (kg)	2100	2100	2200
REAR AXLE PLATED MASS (kg)	3100	3700	4200

■ Passenger seats
 ■ Driver seat
 ■ Opt. Hostess
 ■ Opt. wheelchair
 ■ Seats on rails

FIC EURO VI/C		
MAX POWER	132 kW (180 hp) @ 3500 rpm	107 kW (150 hp) @ 3500 rpm
MAX TORQUE	430 Nm @ 1350 - 3000 rpm	350 Nm @ 1500 - 2900 rpm
DISPLACEMENT	3.0 liters	
4 In-Line cylinders. Unijet Common Rail		

June 2018

IVECO
BUS

BODYWORK / EXTERIOR EQUIPMENT

Anti-corrosion protection by full cathophoretic dipping
 C-section chassis frames linked by tubular cross members
 Manual front door
 Double leaf rear door
 Heated electric rearview mirrors with integrated direction indicators
 R66 compliant

Optional:

- Two models of passenger electric door: forward pivoting door or backward plug door; NP is available only with forward pivoting door
- Anti-pinch device for electric plug door
- Heated electric plug door
- Metallic paint
- Emergency lights operate when the door is opened
- A/C exterior case of same body color

INTERIOR EQUIPMENT

Wooden floor with aluminium finishing
 Floor carpet in anti-slip PVC
 Thermoformed roof passenger compartment
 Leather imitation side wall covering
 ABS window frames covering
 Luggage racks on both sides with white/blue lighting
 Glazed manual roof escape hatch
 Fixed passenger seats with velvet upholstery
 Partition wall on first row of seats
 Separation wall behind driver

Optional:

- Glazed electric roof escape hatch

ELECTRICAL SYSTEM

CAN-bus system with Bodybuilder connector
 12 V – 110 Ah Battery
 150/180 A Alternator
 Daylights

Optional:

- 210 A Alternator
- Emergency central switch
- Fog lights with cornering

WINDOWS / THERMAL COMFORT

Athermal windscreen, single glazing windows
 Thermo-acoustic insulation for roof and side panels
 Driver's place exchange heater driven by 4-speed fan with distribution and recirculation mode
 Passenger heating convector on left hand side

Optional:

- Heated windscreen
- Additional passenger heating on the right side
- Manual or automatic A/C for the driver and passenger throughout air vents in the luggage racks
- Reheating function

DRIVER COMPARTMENT

Soft touch steering wheel: adjustable in height, 390 mm diameter
 Suspended adjustable driver's seat
 Radio CD/DVD with Bluetooth
 Open storage compartment with USB
 Digital tachograph
 LDWS (Lane Departure Warning System)

Optional:

- Leather-trimmed steering wheel
- Suspended adjustable driver seat with lumbar support and heating function
- Driver's airbag
- Cruise control
- Steering wheel controls
- DAB Radio
- Open storage compartment with induction charging and USB
- Parking sensors
- Digital clock

ENGINE

Iveco FIC EURO VI Step C
 Overall displacement: 2998 cc.
 Longitudinal frontal position
 Diesel, 4 In-Line cylinders
 Injection type: Unijet common rail - 16 valves
 Type of turbocharging : VGT (132 kW), WG (107 kW)
 Engine preheating
 DOC + DPF (diesel oxidation catalyst and particulate filter)
 Exhaust after-treatment system: EGR + SCR

Optional:

- HVO (Hydrogenated Vegetable Oil)

GEARBOX

FPT 2840.6 Overdrive mechanical gearbox , 6 gears and reverse
 Single dry plate , pull type clutch, with automatic adjustment

Optional:

- ZF Hi-Matic 8HP

REAR AXLE

Rigid, simple reduction
 Double wheels
 Rear axle ratios: 4.30/4.556/5.13

Optional:

- Differential lock

FRONT AXLE / STEERING

Independent wheels
 Power steering

SUSPENSION

Front:
 QUADTOR with torsion bar and hydraulic telescopic shock absorbers
 Rear:
 Mechanical suspension with dual-leaf parabolic springs and hydraulic telescopic shock absorbers

Optional:

- Air suspension (WABCO – ECAS)

BRAKING SYSTEM

ESP9: includes ABS, ASR, EBD, Hill Holder (HHC), understeering control, emergency braking assistant (HBA), hydraulic fading compensation (HFC)
 Service brake: vacuum assisted hydraulic brake, independent circuits for front and rear axle
 Front and rear disc brakes with pads wear sensors
 Emergency brake: integrated with the service brake
 Parking brake Mechanical
 Telma retarder
 AEBS

FUEL TANK

70 liters shaped diesel tank
 24 liters AdBlue tank

Optional:

- 90 liters diesel tank
- 100 liters diesel tank

TYRES

195/75 R16 (40C/50C)
 225/65 R16 (65C)
 Spare wheel with carrier

Optional:

- Inflation Kit

DISABLED VERSION (OPTION)

Rear underfloor lift, last rows with quick-lock anchorages
 Wheelchair anchorages
 Buttons for stop and door opening request, and driver call