EVADYS

Evadys Single Middle Door 12/13 m - Cursor 9 Diesel and Paraffinic Fuel EURO VI Step E








Length	12 097 mm	12 962 mm
Width	2 550 mm	
Height	3 460 mm	
Wheelbase	6 200 mm	7 065 mm
Front / Rear Overhang	2 605 / 3 292 mm	
Floor height	I 142 mm	
Internal height	1998 mm	
Front / Middle door access height	344 / 344 mm	
Front / Middle door width	800 mm / 800 mm	
Wall-to-wall turning radius	10 770 mm	II 900 mm
Kerb-to-kerb turning radius	8 990 mm	10 120 mm
Approach / Departure angles	8,3° / 8°	
GVW (max permitted weight depends on local legislation)	19 000kg	
Max. weight Front / Rear axle	7 100kg / 12 600kg	
Luggage compartments volume (without or with WC)	8,1/6,7 m ³	9,7/8,3 m ³
Luggage racks volume	1,6 m ³	I,9 m³

CURSOR 9 EURO VI	
Power	294 kW (400 hp) @ 2,200 rpm
Torque	1,700 Nm @1,200 rpm
Displacement	8.7 litres

6 cylinders in line, vertical transverse at the rear, Common Rail




51 + hostess + mini kitchen + WC

Layout 12 m

Up to 53 passenger seats

Layout 13 m



55 + hostess Up to 59 passenger seats

EVADYS

Evadys Single Middle Door 12/13 m - Cursor 9 Diesel and Paraffinic Fuel EURO VI Step E

BODY AND EXTERIOR EQUIPMENT

- Anticorrosion cataphoretic treatment of the structure and of the body, finished with a polyurethane resin final coat.
- Front and middle door 800 mm, I leaf ext. opening
- · Aluminum luggage compartment doors
- · Access to the front lights through opening corners
- · External rearview mirrors, heated, with electrical control

INTERIOR EQUIPEMENT

- Self-adhesive anti-slip PVC carpet on the floor
- Lateral walls and roof covered by artificial leather
- Separation walls covered by upholstery material
- Four buttons "STOP" request
- Passengers seats LINEO Tilting
- Curtains
- Internal luggage racks with individual lights and air outlets
- Passenger area direct lights

ELECTRICAL EQUIPMENT

- LED Lights: front and rear direction lights, rear position lights, rear brake lights, lateral lights and side markers
- Internal LED lights
- · Front Halogen lights, fog lights, DRL LED
- Fire detection system
- Lighting in the luggage compartment
- I 2V/24V sockets on the dashboard

WINDOWS/ THERMAL COMFORT

- · Fixed double glassed windows (horizontal)
- · A/C with heating
- · A/C for driver
- · Two roof hatches, manual control
- Convector heating
- Independent heater
- · Reinforced insulation of sides, front and rear panel

DRIVER'S COMPARTMENT

- · Drivers electric window
- Adjustable driver's seat with air suspension, headrest, 3 pts safety belt
- Lateral and front sun visors with manual control
- · On board computer with fuel consumption control
- Digital tachograph
- Cruise Control
- 2 USB plug
- · Cup holder

Optional:

•Ski box preparation •Towing device preparation •Towing device

Optional:

- Touristic Version: Luggage racks and separations
 R
- · Refrigerator integrated in the dashboard
- Removable carpet on steps and corridor
- Water toilet
- · Passengers seats Spacio
- Hostess box
- · Passenger area indirect lights

Optional:

- Xenon front lights
- · Corner light (integrated in the fog light)
- Warning lights with open doors
- Reverse sensors, reverse camera
- I or 2 LCD monitors 19 inch + 19 inch
- Road camera
- Hostess camera
- USB plugs
- GPS
- Pre disposal for Wifi router

Optional:

Optional:

· LDWS

- Two roof hatches with electrical control
- Reinforced convector heating

· Driver's heating system

Alcohol tester connected

Driver's refrigerator

- · Additional driver's heating on floor
- · Electrical defrosting of the windshield

Front sun visor with electrical control

• Hostess seat with three pts. safety belt

AFTER TREATMENT SYSTEM EVI

• Hi-SCR after treatment system, main components: Diesel Oxydation Catalyst, Diesel Particulate Filter, Selective Catalytic Reduction of Nox with Ad Blue, Clean Up Catalyst.

GEARBOX

Mechanical ZF Intarder

REAR AXLE

- Single reduction hypoid rear axle equipped with "Quiet ride gears set" for low noise
- · Standard axle ratio: 3,70

FRONT AXLE/ STEERING

- · Front axle with independent wheels suspension
- · Worm-type steering with integrated power steering

SUSPENSION

- Full air suspension with self- levelling sensor
- Front: 2 combined air springs/2 shock absorbers/1 levelling sensor
- Rear: 4 air springs/4 shock absorbers /1 stabilization bar/2 levelling sensors

COMPRESSED AIR

- Dual cylinder air compressor 630 cm3 (pressure 9,5 bar)
- Integrated air dryer: bleeding valves on the air tanks

SAFETY / BRAKES

- EBS/ESP
- Pneumatic service and emergency braking system with two independent air circuits.
- $\cdot\,$ Brake discs, front and rear, with floating calipers and ABS
- · Pneumatic parking brake, operating on the rear wheels
- · Automatic fire extinguisher in engine compartment

RETARDER

- Decompression engine brake
- · Intarder with brake pedal control and hand lever control,

FUEL TANK AND UREA TANK

- 310 lt. diesel tank
- 80 lt. Ad Blue tank

TYRES AND WHEELS

- · 295/80 R 22,5 tyres
- · Spare wheel carrier in the front overhang

Optional: • Automatic Voith DIWA Next

Optional:

Optional:

Ontional:

Optional:

gearbox

Optional

Optional

Optional

Iveco Bus works with a constant evolution and reserves the right to make changes to its product without prior notice

· 310+120 lt. tank

Aluminum wheel rims

suspensions

Automatic ZF ECOLIFE
Robotized ZF TRAXON
E-Horizon with Traxon gearbox

• Other rear axle ratios available

· Axles load indicator (OBW)

· Axles load indicator (OBW)

· Lifting/Lowering of the vehicle's

AEBS / ACC with ZF automatic &

Hydraulic integrated retarder

Hillholder with ZF Traxon robotized

robotized gearboxes

Reinforced shock absorbers

Tél.:

- France .

des Combats du 24 Août 1944 - 69200 Vénissieux

- 1 Rue o

Edition February 2021 - IVECO France

IVECO

Drive the road of change